

Features:

- Standard H.265 compression, low bit rate, high image quality
- Support 16CH 5M/4M/1080P/720P/AHD/TVI/CVI/WD1 Input
- Mouse control OSD/PTZ function
- Panel with individual light for recording, internet, power and backup
- Support multi passwords protection and user control
- Support 2USB / internet backup
- Monitoring and playback, camera name in English or 15 Chinese characters supported
- 4G phone remote review (Android/iphone/iPad)
- Support 4 channels IP camera input/ maximum switchable to 12 CH IP input
- Support remote image playback function



CV-ATR508H 8CH 5MP Hybrid Video Recorder

Display Rate	5MP@160fps;4MP/3MP/1080P/720P/WD1 @240fps
Recording Rate	5MP Lite@80fps/4MP Lite@96fps/ 1080P(1920x1080)@120fps/720/WD1(960x480)@240fps
	Each channel recording rate adjustable
Display Channel	1/4/6/8/9/16 split screen; Sequence Display; x7 digital zoom
Recording Mode	Manual/24hrs/Schedule/Motion/Alarm/24hrs+motion 24hrs+alarm/24hrs+motion alarm
Record Quality	Main Stream:768kb~8Mbps/Sub Stream:128kb~1024kb
Playback Mode	Date & Time search / Filing Time search / Event search
Playback Speed	Fast Forward & Backward: x1, x2, x4, x8, x16, x32
Playback	Host:8CH/Remote:4CH
OSD Display	HD data, Timing, Camera & Recording setting, MENU function setting
Video Input	8CH Input (4 ways mixable)+4CH IPCam Input
Video Output	CVBS(Spot)x1/VGAx1(1920x1080)/HDMI(1920x1080)
Audio In / Out	8CH (RCA) / 1CH
Remote Control / Mouse	Standard
Motion Detect	22 x 18 grids camera for all channel
Alarm In / Out	8CH IN / 2CH OUT
RS-485	PTZ Control PELCO-P, PELCO-D
E-SATA	Support 1 group
Internal HDD Support	3.5" SATA HD x 1 (Each HD Support up to 10T)
Network Function	IE browser/Chinese 100CH CMS
Power Source	DC12V , 50Hz/60Hz
Weight	N. W. / G. W. : 0.7kg/0.85kg (HD excluded)
Dimension	300(W)mm x 55(H)mm x 270(D)mm