
Features:

- Standard H.265 compression, low bit rate, high image quality
- Support 16CH 5M/4M/1080P/720P/AHD/TVI/CVI/WD1 Input
- Mouse control OSD/PTZ function
- Panel with individual light for recording, internet, power and backup
- Suport multi passwords protection and user control
- Support 2USB / internet backup
- Monitoring and playback, camera name in English or 15 Chinese characters supported
- 4G phone remote review (Android/iphone/iPad)
- Support 8 channels IP camera input/maximum switchable to 16 CH IP input
- Support remote image playback function



Display Rate	5MP@320fps;4MP/3MP/1080P/720P/WD1@480fps
Recording Rate	5MP Lite@160fps/4MP Lite@196fps/
	1080P(1920x1080)@240fps/720/WD1(960x480)@480fps
	Each channel recording rate adjustable
Display Channel	1/4/6/8/9/16/25 split screen; Sequence Display;
	x7 digital zoom
Recording Mode	Manual/24hrs/Schedule/Motion/Alarm/24hrs+motion
	24hrs+alarm/24hurs+motion alarm
Record Quality	Main Stream: 768kb~8Mbps/Sub Stream:128kb~1024kb
Playback Mode	Date & Time search / Filing Time search /
	Event search
Playback Speed	Fast Forward & Backward: x1, x2, x4, x8, x16, x32
Playback	Host:16CH/Remote:4CH
OSD Display	HD data, Timing, Camera & Recording setting,
	MENU function setting
Video Input	16CH Input (4 ways mixable)+8CH IPCam Input
Video Output	CVBS(Spot)x1/VGAx1(1920x1080)/HDMI(1920x1080)
Audio In / Out	8CH (RCA) / 1CH
Remote Control / Mouse	Standard
Motion Detect	22 x 18 grids camera for all channel
Alarm In / Out	16CH IN / 4CH OUT
RS-485	PTZ Control PELCO-P, PELCO-D
E-SATA	Support 1 group
Internal HDD Support	3.5" SATA HD x 2 (Each HD Support up to 10T)
Network Function	IE browser/Chinese 100CH CMS
Power Source	DC12V, 50Hz/60Hz
Weight	N.W. / G.W.: 0.8kg/1.0kg (HD excluded)
Dimension	380(W)mm x 52(H)mm x 270(D)mm